



meters uk Ltd TM

Utility Meter Manufacturers

ELECTRICITY – GAS – HEAT – WATER METERS

FLEXi REXi

Flexible Connectors – Making Life Easy – Gas Installations

- ✓ Manufactured to DIN 30681 –
- ✓ Tested according to ISOEN 10380
- ✓ Certified in compliance with PED 9723CE –
(European Directive concerning equipment under pressure)



Flanged to PN 16 Fixed End & Swivel – Easy Fit End Flanges & Bellows – Carbon Steel

FLEXi REXi – Description & Sizes				
Order Code	Description	End 1	End 2	Length
FRFLG50	50mm ss corrugated annealed fitted mild steel – Flanges welded on	50mm FI PN16 Fixed	50mm FI PN16 Swivel	300mm
FRFLG80	80mm ss corrugated annealed fitted mild steel – Flanges welded on	80mm FI PN16 Fixed	80mm FI PN16 Swivel	350mm
FRFLG100	100mm ss corrugated annealed fitted mild steel – Flanges welded on	100mm FI PN16 Fixed	100mm FI PN16 Swivel	350mm
FRFLG150	150mm ss corrugated annealed fitted mild steel – Flanges welded on	150mm FI PN16 Fixed	150mm FI PN16 Swivel	426mm
FRFLG200	200mm ss corrugated annealed fitted mild steel – Flanges welded on	200mm FI PN16 Fixed	200mm FI PN16 Swivel	470mm

www.meters.co.uk

meters uk Ltd, Whitegate, White Lund Trading Estate, Lancaster, Lancashire LA3 3BT

Tel: 01524 555929 Fax: 01524 847009

FLEXi REXi

Flexible Connectors – Making Life Easy – Gas Installations

FLEXi REXi – Flexibility Data --suitable for installation with **GOLDi Turbine Gas Meters**

mm size	tube size	NP16 fixed	NP16 swivel	length	overall length	length tolerance	max wp	min bend radius	Total max offset
50mm	2"	2"	2"	219mm	300mm	+.2% or -1%	1 bar @20C	350mm	16mm
80mm	3"	3"	3"	264mm	350mm	+.2% or -1%	1 bar @20C	525mm	15mm
100mm	4"	4"	4"	264mm	350mm	+.2% or -1%	0.7 bar @20C	625mm	15mm
150mm	6"	6"	6"	340mm	426mm	+.2% or -1%	0.5 bar @20C	900mm	15mm
200mm	8"	8"	8"	384mm	470mm	+.2% or -1%	0.3 bar @20C	1020mm	15mm

